

WHAT IS CLAIMED IS:

1. A method for datagram staggering in a communication system, comprising:

receiving samples of a first input signal and a second input signal, the first input signal corresponding to a first communication device, the second input signal corresponding to a second communication device;

generating a first plurality of datagrams containing at least a portion of the samples of the first input signal; and

generating a second datagram containing at least a portion of the samples of the second input signal, the second datagram staggered from each of the first plurality of datagrams such that the second datagram is ready for communication at a different time than any of the first plurality of datagrams.

2. The method of Claim 1, wherein generating the second datagram such that the second datagram is staggered from each of the first plurality of datagrams comprises staggering the second datagram from at least one of the first plurality of datagrams by a predetermined amount of time, the predetermined amount of time approximately equal to a communication time of one of the first plurality of datagrams.

3. The method of Claim 1, wherein generating a first plurality of datagrams comprises generating one of the first plurality of datagrams at or near a time when a first threshold number of samples of the first input signal are received; and

wherein generating a second datagram comprises generating the second datagram at or near a time when a second threshold number of samples of the second input signal are received.

09705562 "110200

4. The method of Claim 3, wherein receiving samples of a second input signal and generating a second datagram such that the second datagram is staggered from each of the first plurality of datagrams comprises:

5 determining a first value for the second threshold number of samples;

receiving a number of samples of the second input signal, the number of samples approximately equal to the first value of the second threshold number;

10 discarding the received samples; and

determining a second value for the second threshold number of samples.

15 5. The method of Claim 1, wherein receiving samples of a first input signal and a second input signal comprises:

receiving at least a portion of the samples of the first input signal over a first communication channel; and

20 receiving at least a portion of the samples of the second input signal over a second communication channel.

6. The method of Claim 5, wherein generating the second datagram such that the second datagram is staggered from each of the first plurality of datagrams comprises:

25 starting a timer at or near a time when one of the first plurality of datagrams is ready for communication; and

establishing the second channel at or near a time when the timer elapses.

30

7. The method of Claim 6, wherein the timer is started by an interrupt associated with the first communication channel; and

35 wherein the second communication channel is established in response to a timer completion interrupt.

09705552-110200

5 8. The method of Claim 1, wherein receiving samples of a first input signal and a second input signal comprises receiving the samples over a bus, the bus operable to support communication over a plurality of communication channels.

10 9. The method of Claim 8, wherein the bus comprises a plurality of windows; and
further comprising establishing an active channel using one of the windows at or near a time when one of the communication devices becomes active.

15 10. The method of Claim 9, wherein a first active channel uses a first window of the bus; and
wherein another active channel uses a first available window following an occupied window of the bus.

20 11. The method of Claim 10, wherein the other active channel is established at or near a time when a timer elapses.

25 12. The method of Claim 1, further comprising generating the samples of the first and second input signals.

30 13. The method of Claim 12, wherein generating the samples of the first and second input signals comprises generating the samples of the first and second input signals using different compression methods.

14. The method of Claim 1, wherein each of the datagrams comprises an Asynchronous Transfer Mode (ATM) cell containing a predetermined number of samples.

09705562-110200

15. A system for datagram staggering in a communication system, comprising:

at least one computer readable medium; and

software encoded on the computer readable medium, the
5 software operable when executed to:

receive samples of a first input signal and a second input signal, the first input signal corresponding to a first communication device, the second input signal corresponding to a second communication device;

10 generate a first plurality of datagrams containing at least a portion of the samples of the first input signal; and

generate a second datagram containing at least a portion of the samples of the second input signal, the second datagram staggered from each of the first plurality of datagrams such that the second datagram is ready for communication at a different time than any of the first plurality of datagrams.
15

20 16. The system of Claim 15, wherein the software is operable to generate the second datagram such that the second datagram is staggered from each of the first plurality of datagrams by staggering the second datagram from at least one of the first plurality of datagrams by a
25 predetermined amount of time, the predetermined amount of time approximately equal to a communication time of one of the first plurality of datagrams.

30 17. The system of Claim 15, wherein the software is operable to generate one of the first plurality of datagrams at or near a time when a first threshold number of samples of the first input signal are received; and

wherein the software is operable to generate the second datagram at or near a time when a second threshold
35 number of samples of the second input signal are received.

09705562-110200

18. The system of Claim 17, wherein the software is operable to receive samples of the second input signal and generate the second datagram such that the second datagram is staggered from each of the first plurality of datagrams by:

determining a first value for the second threshold number of samples;

receiving a number of samples of the second input signal, the number of samples approximately equal to the first value of the second threshold number;

discarding the received samples; and

determining a second value for the second threshold number of samples.

19. The system of Claim 15, wherein the software is operable to receive samples of the first and second input signals by:

receiving at least a portion of the samples of the first input signal over a first communication channel; and

receiving at least a portion of the samples of the second input signal over a second communication channel.

20. The system of Claim 19, wherein the software is operable to generate the second datagram such that the second datagram is staggered from each of the first plurality of datagrams by:

starting a timer at or near a time when one of the first plurality of datagrams is ready for communication; and

establishing the second channel at or near a time when the timer elapses.

09705562-110200

5

10

15

20

25

30

35

28. A modem, comprising:

a memory operable to receive and store at least a portion of samples of a first input signal and a second input signal, the first input signal corresponding to a first communication device, the second input signal corresponding to a second communication device; and

a processor coupled to the memory, the processor operable to:

receive the samples from the memory;

generate a first plurality of datagrams containing at least a portion of the samples of the first input signal; and

generate a second datagram containing at least a portion of the samples of the second input signal, the second datagram staggered from each of the first plurality of datagrams such that the second datagram is ready for communication at a different time than any of the first plurality of datagrams.

29. The modem of Claim 28, wherein the processor is operable to generate the second datagram such that the second datagram is staggered from each of the first plurality of datagrams by staggering the second datagram from at least one of the first plurality of datagrams by a predetermined amount of time, the predetermined amount of time approximately equal to a communication time of one of the first plurality of datagrams.

30. The modem of Claim 28, wherein the memory comprises a first buffer corresponding to the first communication device and a second buffer corresponding to the second communication device.

09705562 110200

31. The modem of Claim 28, wherein the processor is operable to generate one of the first plurality of datagrams at or near a time when the memory receives a first threshold number of samples of the first input signal; and

wherein the processor is operable to generate the second datagram at or near a time when the memory receives a second threshold number of samples of the second input signal.

32. The modem of Claim 31, wherein the processor is operable to stagger the first plurality of datagrams and the second datagram by:

determining a first value for the second threshold number of samples;

allowing the memory to receive a number of samples of the second input signal, the number of samples approximately equal to the first value of the second threshold number;

discarding the received samples; and
determining a second value for the second threshold number of samples.

33. The modem of Claim 28, wherein the memory is operable to receive the samples by:

receiving at least a portion of the samples of the first input signal over a first communication channel; and

receiving at least a portion of the samples of the second input signal over a second communication channel.

34. The modem of Claim 33, wherein the processor is operable to stagger the first plurality of datagrams and the second datagram by:

5 starting a timer at or near a time when one of the first plurality of datagrams is ready for communication; and

establishing the second channel at or near a time when the timer elapses.

10 35. The modem of Claim 34, wherein the timer is started by an interrupt associated with the first communication channel; and

15 wherein the second communication channel is established in response to a timer completion interrupt.

20 36. The modem of Claim 28, wherein the memory is operable to receive the samples over a bus, the bus operable to support communication over a plurality of channels.

25 37. The modem of Claim 36, wherein the bus comprises a plurality of windows; and

wherein the processor is operable to establish an active channel using one of the windows at or near a time when one of the communication devices becomes active.

30 38. The modem of Claim 37, wherein a first active channel uses a first window of the bus; and

wherein another active channel uses a first available window following an occupied window of the bus.

35 39. The modem of Claim 38, wherein the other active channel is established at or near a time when a timer elapses.

09705562 110200

40. The modem of Claim 28, wherein the first and second input signals are generated using different compression methods.

5 41. The modem of Claim 28, wherein each of the datagrams comprises an Asynchronous Transfer Mode (ATM) cell containing a predetermined number of samples.

09705562 110200